





**DO NOT ACCEPT COPIES, BUT GO FOR THE ORIGINAL ONLY.
PTR HOLLAND® GROUP, ORIGINATOR OF THE PILOT / EMBARKATION LADDER CLAMPING SYSTEMS.**



- Steps have non-skid / anti-slip surface.
- The side ropes of the embarkation ladder consist of two uncovered mildew resistant manila ISO1181:2004 ropes not less than 20mm in diameter (63mm circumference) on each side, with no joints and have a breaking strength of at least 24kN per side rope.
- All our embarkation ladders are built with pure manila A grade rope, on request can be built with Polyprop- ("orange") or White PP/PES mix rope as well.
- The midpoint half-length being located on a thimble large enough to accommodate at least two passes of side rope.
- Steps are secured with PTR's patented sea water resistant aluminium clamping system according to ISO 209
- Two RVS316 wire rope thimbles are provided at the top of the ladder.

Producer:	PTR HOLLAND GROUP	Material:	HARDWOOD		
Title:	THETIS EMBARKATION LADDER	Approval:	M.E.D. according DIN/ISO 5489:2008 / SOLAS 74		
Drawing:	WLEL9-28	Components:	28 Steps		
 ROTTERDAM · SINGAPORE · HOUSTON · NEWCASTLE · PIRAEUS  The mark of responsible forestry FSC® C126587 	 MED DNV-GL:0575	Weight:	56 kg	Scale:	
		Date:	31-Aug-2022	Size:	A4
		Drawn By:	BLS-Engineering.com	Units:	mm
		Drawing number:	8-1112-0109	Rev.	D