

~	
5	

(d. width) aut aut in steel	naaf toggles	no di	breaking stress	Allowed pos.
-		inshippos. 1 and 2	hinges	kŊm	Reg. 13 of ICL
605	625-625	1	2	330	182
800	823-820	2	2	189	182
700	920×720	2	2	192	182
600	1020-620	2	2	202	1&2
600	1220×620	2	2	168	182
890	1220×850	4	2	119	182
600	1320-620	4	2	155	182
600	1420×620	4	2	144	1&2
700	1420×720	4	2	123	182
800	1470×820	4	2	104	1&2
900	1420-920	4	2	96	1&2
600	1620×620	4	2	126	1&2
650	1580-670	4	2	119	1&2
700	1620×720	4	2	108	1&2
750	1620×770	4	2	101	182
800	1620-820	4	2	95	182
900	1620×920	4	3	84	182
800	1670×820	4	2	92	182
650	1720-670	4	2	109	182
700	1720×720	4	2	102	182
900	1720×920	4	2	79	2
600	1820×620	4	2	112	182
650	1820-670	4	2	103	182
700	1820-720	4	2	96	182
750	1820×770	4	2	90	182
800	1820-820	4	2	84	182
800	1900×820	4	3	80	1&2
900	1820-920	4	3	75	2
700	1920-720	4	3	91	1&2
800	1920-820	4	3	80	2
830	1950×850	4	3	76	2
900	1920-920	4	3	71	2
900	1970-920	4	3	69	2
1000	1920x1020	4	3	64	2
1020	1820x1040	4	3	66	2
1070	1820×1090	4	3		2
700	2020×720	4	3		2
800	2020×820	4	3	76	2
800	2070×820	4	3	74	2
1084	2104×1104	4	3	54	2

	Drawn	Checked	Project:	
Date				
 Name			Customer:	
 Name Kunststofftechnik Julitz GmbH Tel. 0049(0)4161 4494 Fax 0049(0)4161 4485			Designation: Heavy weathertight GRPoutside door with central closing system Drawing No. 64/	A
1 ux 00	17(0)+101 +	105	04/	