



# ELITE

SYSTEM  
**2**

Recyclable "anywhere floor.  
No nails, no glue.

## Usage areas

Bergo Flooring has developed a wide range of flooring products for different environments.

Elite is specially developed for usage areas such as: Office environments, conservatories, terraces, storage rooms, recreation/hobby-rooms and other residential applications.

## Advantages

- Easy to install
- Ventilates the floor underneath
- Can be used both indoors and out
- Moveable
- Easy to keep clean
- Attractive, durable and practical!
- Possible to achieve various designs

## Easy to install and move

Tapping a rubber mallet or similar over the protruding rings easily interlocks the tiles together. No special tools, glue or screws are required. If necessary, use a jig- or a circular-saw to cut the tiles for a perfect fit.

The Bergo tile is easy to move by using a Disassembly-tool (see picture). For an increased comfort a suitable sound absorbing foam underlay may well be used underneath the ELITE tiles. Remember to choose a permeable foam for Bergo ELITE laid on a damp floor that needs to breathe, such as concrete.

## Easy to keep clean

Bergo tiles require virtually no maintenance. Normal floor care such as occasional wiping with a damp cloth, vacuuming and/or hosing is usually all that is needed. The Elite tile can stay outside in both summer and winter.

## Accessories



- Edge strip – 376 x 55 mm, for a smart and safe finish.
- Corner strip – 55 x 55 mm.
- Decor/Cable strip – 376 x 55 mm, for special design purposes and/or hiding cables underneath the flooring.
- Decor/Cable cross-piece – 55 x 55 mm, to be used as two lines of the above Decor/Cable strips intersect with each other.
- Joint strip – 378 mm, for decoration and closing joints.

The rubber joint strip are installed in between each ELITE tile in order to create a completely covered surface. The rubber joint strip should only be used indoors or as one have a constant temperature where the flooring are being installed. As one have temperature variations the expansion gap between the tiles needs to be open.

## Technical information

Material:	Environmentally friendly recyclable
Size of tile:	UV-stabilised polypropylene.
Thickness of tile:	380 x 380 mm.
Packaging:	10,2 mm. 1 m <sup>2</sup> / carton = 7 tiles.
Colours:	5 m <sup>2</sup> / carton = 35 tiles Various standard colours.

MADE IN SWEDEN



Edge strips and Corner strip

Decor/Cable strips

Easy to cut

Disassembly-tool