












TECHNICAL INFORMATION / TEKNISK INFORMATION



BERGO XL

Material:		ISO2076	Environmentally friendly recyclable UV-stabilized polypropylene.	/ Miljövämlig återvinningsbar UV-stabiliserad polypropen.
Size of tile: /Plattans storlek:		EN427	377,2 x 377,2 mm. 1 m ² / box = 7 tiles. 5 m ² / box = 35 tiles.	
Thickness of tile: /Plattans tjocklek:		EN428	10,1 mm.	
Weight: /Vikt:		EN430	1 tile: 0,350 kg. 1 m ² : 2,63 kg (Consumer pack). 5 m ² : 12,85 kg (Maxi-pack).	
Point load: /Punktbelastning:		QUALIFIED TEST BY BERGO	250 ton / 1 m ² = 2500 kg/dm ²	
Light fastness: /Ljusbeständighet:		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8	
Weather Fastness /UV- Florida test (1-5):		ASTM D1435 ASTM G154 Cycle A	4/5	
Slip resistance: /Halkmotstånd:		SSEN-13893	>0,3	
Impact resistance: /Slagtålighet:		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C15 kJ/m ²	
Fire category /Brandklassning:		EN ISO 11925-2	E _{fl}	
CE certification:		EN 14041	0402-CPD-P605080A	

Packaging:	Quantity / packaging unit:	Quantity / pallet:	Size of pallet:
Consumer-pack	1 m ² = 7 tiles	1 pallet = 90 cartons = 90 m ²	1,20 x 0,80 x 1,23 m = 1,18 m ³ , 262 kg gross weight
Maxi-pack	5 m ² = 35 tiles	1 pallet = 36 cartons = 180 m ²	1,20 x 0,80 x 2,41 m = 2,31 m ³ , 480 kg gross weight




By normal use and treatment the material guarantee time is 10 years.



Bergo Flooring AB fulfills the requirements of ISO 9001.



Bergo Floors are 100% recyclable.



SYSTEM
2

www.bergoflooring.com

