

# NIGHTSTICK®

## Intrinsically Safe Dual-Function Headlamp

This dual-function headlamp is cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe. The headlamp features a multi-position tilt head design and include an elastic head strap with a non-slip lining and a heavy-duty rubber head strap for use on a hard hat. The top mounted switch provides user selectable high or low brightness spotlight operation. Power comes from 3 AAA premium batteries (included).

**INTRINSICALLY SAFE**

**60/40 Lumens  
Spotlight**

Spot High



Spot Low



- cETLus, ATEX, IECEx and INMETRO listed Intrinsically Safe
- High/low-brightness spotlight
- 80/92 Meter beam distance
- Engineered polymer housing



**XPP 5450G**

### Intrinsically Safe Dual-Function Headlamp

XPP-5450G



#### XPP-5450G SPECIFICATIONS

- Lumens: high spotlight-60, low spotlight-40
- Run-time: high spotlight-13.5 hrs, low spotlight-22.75 hrs
- Beam distance: 80 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Width: 2.4in, height: 1.9in, depth: 1.8in, weight: 3.5oz

#### FEATURES

- CREE® LED technology – 50,000 + hours LED life
- High-brightness spotlight, low-brightness spotlight
- Focused spotlight beam for distance illumination
- Engineered polymer housing
- Single switch located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Heavy-duty rubber strap for hard hat applications
- Waterproof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)
- Limited Lifetime Warranty\*

FL1 STANDARD	HIGH	LOW
	60 LUMENS	40 LUMENS
	13h	23h
	80m	65m
	1615cd	1076cd
	2m	
	1m	

#### SAFETY RATING

cETLus, ATEX and IECEx listed Intrinsically Safe

Patent 7,738,229

#### INCLUDED

- Headlamp
- 3 Premium alkaline AAA batteries
- Elastic non-slip head strap
- Heavy-duty rubber hard hat strap



Heavy-duty rubber head strap

**Nightstick 5450 Headlamp**

**Intertek**

ID 4001184  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

**Seguranca**

CLASS I DIV 1 GRPS A-D T3 Ex ia IIC T3 Ga  
 CLASS II & III GRPS E-G T135C Intertek ITS 13 ATEX27854X  
 CLASS I ZONE 0 AEx ia IIC T3 Ga IECEx ETL 13.0031X  
 CLASS I ZONE 0 Ex ia IIC T3 Ga -20°C ≤ Tamb ≤ +40°C  
 II 1 G Ex ia IIC T3 Ga 1.5V/Cell AAA Alkaline

CE 0359

---

**Conforms to:**  
 ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11, ANSI/ISA 60079-26

**Certified to:**  
 CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

Model	UPC 0 17398
XPP-5450G	80300 7

\*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.