# **AMEROID® OWS**



#### **DESCRIPTION**

AMEROID OWS quick separating degreaser is a superior solvent emulsifying detergent for general engine room degreasing and for cleaning and gas freeing of bilges. Its unique blend of surfactants, wetting agents, and solvents results in a product which has exceptional cleaning properties, breaks quickly, and does not harm the operation of oily water separators required under the MARPOL regulations.

AMEROID OWS has been thoroughly tested and is approved by the following separating and bilge alarm manufacturers.

- · Biospherics Incorporated
- · Blohm & Voss AG
- · Butterworth Systems (UK) Ltd.
- Hamworthy Engineering Ltd.
- · Hodge Separators Limited
- Italgestra S.P.A.
- National Fluid Separators, Inc.
- · Nelson Division, Nelson Industries
- Quantek, Inc. (Facet Enterprises)
- SFRFP
- · Separation and Recovery Systems, Inc.
- Sigma Treatment Systems
- World Water Systems, Inc.
- Approved for use onboard U.S. Coast Guard vessels

### **APPLICATION**

Typical cleaning solution strength will vary from 0.1% - 10% depending upon the type soil and the method of cleaning.

AMEROID OWS may be diluted with fresh or seawater, depending upon the cleaning required. If the spent cleaning solution is to go through an oily water separator, ensure that the concentration does not exceed recommended levels set by the separator manufacturer. The level which is recommended by those manufacturers testing and recommending AMEROID OWS degreaser is generally 0.1%. If possible, allow time for settling and separation of waste water and oil to occur. This will enhance separator operation.

#### **GENERAL DEGREASING**

For general purpose cleaning and degreasing, use AMEROID OWS neat or diluted to a 5% concentration, depending on the type soil to be cleaned. Apply the cleaning solution by brushing or swabbing. Allow the solution to penetrate the soil, then rinse with warm water, 40°- 60° C. When using mechanical spray units, AMEROID OWS degreaser may be used in concentrations as low as 0.1%, depending upon soil conditions.

#### **BILGE CLEANING**

To clean oil from bilges by the rock-and-roll method, add AMEROID OWS® at one or more locations in the bilge at the approximate dosage level indicated in the table below. Add seawater to fill approximately 1/3 of the bilge capacity to form a 0.1% cleaning solution. Allow the natural rock-and-roll motion of the vessel to provide agitation for a minimum of 24 hours. At the end of 24 hours, pump the bilge in accordance with normal procedures. Inspect; and if required, repeat the procedure or spot clean.

#### **FEATURES**

- · Quick-breaking emulsifiers
- · Solvent-emulsifying cleaner
- Concentrated Solvents
- · Liquid formulation

#### **BENEFITS**

- · Reduces the potential of oil discharge
- Does not contribute to OWS operating problems and false alarms
- · Allows oil to separate from water
- · Reduces slop disposal costs
- · Readily disperses in water
- · Reduces cleaning time
- · Cost effective
- Minimizes manual cleaning
- · Easy to apply

**Contact your Drew Marine representative for more information** 



## **TYPICAL PROPERTIES**

Appearance: Clear, light amber

Specific Gravity @25°C: 0.88 Flash Point (closed cup): 65° C min.

**NOTE:** Always wear the appropriate personal protective equipment when using this product.

## **PACKAGING**

AMEROID OWS quick separating degreaser is available in 25-liter containers (PCN 0016403).

## **IMPORTANT INFORMATION**

Drew Marine maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees.

Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.

Continued on Page 3

Drew Marine maintains Safety Data Sheets on all of its products. These documents contain health and safety information for the development of appropriate product handling procedures to protect your employees. Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.



100 South Jefferson Road Whippany, NJ 07981 USA 1-973-526-5700 Drew-Marine.com

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.