

CODE: MBK03-300CA-P1A

ERP: 0129001

## Trolley Fire Extinguisher 30Kg CO2 Trolley

**30Kg** CO2 Trolley Fire Extinguisher with 40Lt Cylinder with 5m Discharge Hose.

HIGH-PRESSURE EPDM Discharge Hose of WP 155bar with Wooden Handle and Flow Control Valve, according to EN853 requirements, HEAVY Duty Carriage and wheels, Valve Protection HANDLE  
All CO2 Trolley Fire Extinguishers are also available with 8 meter discharge hose upon request



### CHARACTERISTICS

Capacity	30Kg
Extinguishing Agent	CO2
Operating Temperature	-20 to+60 °C
Max Allowable Pressure	192 bar
Test Pressure	300 bar
Volume of Equipment	40 lt
Cylinder Height	1230±30 mm
Cylinder Diameter	229±2,29 mm
Cylinder Neck Thread	25E
Cylinder Material	34CrMo4
Valve Material	HPb59-1
Safety Valve	250-275 bar
Approx. gross Weight	80 kg
Approx. Dimensions	1400x500 mm
Paint Finish	RAL 3000
Packaging Details	1 pc

Issue Date: 16/08/2021

2010/35/EU (r)

EN1866



EN1964

Information may change

**FACTORY:** AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

**CENTRAL EXHIBITION:** 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

**ATHENS DISTRIBUTION CENTER:** SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

**N.GREECE DISTRIB. CENTER:** 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

**CENT. & EAST CRETE DISTRIB. CENTER:** P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

[www.mobiak.com](http://www.mobiak.com)