

CODE: MBK09-120PA-DF

ERP: 0135216

Fire Extinguisher 12Kg Dry Powder Portable

Fire Extinguisher 12Kg with one seam vessel Pressure Gauge Safety Release Valve.

- METALLIC BRACKET INCLUDED

Instructions for use printed on a sticker



CHARACTERISTICS

Capacity	12Kg
Extinguishing Agent	ABC 40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	13Lt lt
Cylinder Height	535 ± 5 mm
Cylinder Diameter	190 ± 1.5 mm
Cylinder Neck Thread	M30 ± 1.5mm
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	18,14 kg
Approx. Dimensions	700 x 280 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



Issue Date: 09/03/2022

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiakfire.com