

DESCRIPTION

DREWPLUS ED-795 is a water-based defoaming compound that has been specifically formulated for controlling foam in evaporative desalination equipment. U.S. manufactured DREWPLUS ED-795 is certified by NSF International to NSF/ANSI Standard 60, as an antifoam to be added to the feed water for evaporative desalination units up to 20 ml/ton of rated capacity.

APPLICATION & USE

DREWPLUS ED-795 may be added neat or combined with Ameroyal evaporator treatments to defoaming applications using a DREW Beta Metering System (PCN 1AA8978) and the DREW Gravity Metering System (PCN 1AA8977).

The recommended dosage is 5ml per ton of distilled water produced per day based on the rated capacity at normal operating temperature and brine density. If foaming persists at this dosage, increase the feed rate by 1 ml per ton until control is achieved.

For best results, store at 10-32° C (50-90° F). Should the product freeze, allow it to warm to the above temperatures and mix thoroughly before use.

Unlined mild steel, black iron, galvanized steel, aluminum, copper or brass should not be used in any part of the feed system. For pump heads and feed lines, stainless steel, TEFLON1, VITON1, PVC, neoprene or TYGON2 materials are recommended.

EVAPORATOR DOSAGE CHART

Rated Capacity (Tons)	Dosage
5	25.0 ml
10	50.0 ml
50	250.0 ml
100	0.5 liters
1000	5.0 liters

TYPICAL PROPERTIES

Appearance:	Clear colorless liquid
Flash Point:	None
Freeze Point (undiluted):	0°C (32°F)
pH (undiluted):	7.5
Specific Gravity @ 25° C(77° F):	1.02

NOTE: Always wear the appropriate personal protective equipment when using this product.

PACKAGING

DREWPLUS ED-795 is available in 25-liter containers (PCN 1679408).

IMPORTANT INFORMATION

Drew Marine maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees.

Our Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.

FEATURES

- Effective defoaming compound
- Liquid formulation
- Low dosage
- Certified to NSF/ANSI Standard 60

BENEFITS

- Improved distillate quality
- Easy to feed
- Economical
- Safe to use



Contact your Drew Marine representative for more information

Drew Marine maintains Safety Data Sheets on all of its products. These documents contain health and safety information for the development of appropriate product handling procedures to protect your employees. Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Drew Marine products.



Drew Marine®

**100 South Jefferson Road
Whippany, NJ 07981 USA
1-973-526-5700
Drew-Marine.com**

Copyright © Drew Marine. All Rights Reserved. All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, express warranty or implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which seller assumes legal responsibility, and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.