

Altrex RS TOWER 52

Double-width modular mobile access tower for intensive professional maintenance. The selection below uses 2.45 m Fiber-Deck platforms and Safe-Quick guardrails with braces.

Technical overview

Frame width	1.35 m
Selected platform length	2.45 m
Selected working heights	4.20 / 6.20 / 8.20 / 10.20 m
Maximum load per platform	250 kg
System	Modular RS TOWER 5

Selected configurations

Working height	Platform	Configuration ID
4.20 m	2.45 m Fiber-Deck	2629
6.20 m	2.45 m Fiber-Deck	2631
8.20 m	2.45 m Fiber-Deck	2633
10.20 m	2.45 m Fiber-Deck	2635

Selection and documentation

Working height is not platform height. Assembly, stabilisers, guardrails, loads and permitted indoor/outdoor heights must follow the Altrex manual for the complete configuration. Current Altrex tower configurations are designed around EN 1004 requirements. Configuration IDs identify Altrex website selections; they are not orderable article numbers. Component article numbers are confirmed with the final quotation.

Prepared by MariTeam from Altrex product specifications. This product summary is not an Altrex certificate or assembly manual. Data reviewed 8 September 2026.

Source: altrex.com/en/scaffolding/rs-tower-52-mobile-access-tower/2599