

Mounter[®]

- Rope-operated ladder or combination ladder
- Coated I-profiled ladder, for intensive, professional use
- Comfortable in use thanks to non-skid D-shaped rungs (45 mm deep)
- Easy to handle along the facade thanks to top rollers and the swivel hook
- Automatically locking swivel hook



EN 131


PROFESSELEEL
ARBO GEBRUIK
NEN 2484

DEKRA

Mounter®. The top of the range ladder for professionals

The Mounter® is equally strong as stable. The light weight I-profile is specifically designed for intensive use. The unique D-shaped rung is firmly in place thanks to its special shape. Moreover, the deep standing surface gives you more standing comfort and the stabiliser beam also provides additional stability. The distinctive black coating is also another nice addition to dirt repellent.

This rope-operated 2-part ladder is also ideal for working against a façade. The extendible ladder is easy to use due to the rope/pulley system and the top rollers at the ends. With one simple movement, the ladder slides out to its extended length. Perfect for every job.



MOUNTER® ROPE-OPERATED LADDER - aluminium ladder (black coated)

Description	Art.no.	Type	Number of rungs	Storage length (m)	Extended length (m)	Max. working height (m)	Weight (kg)
2-part rope-operated ladder	124816	ZS 2080	2 x 16	4.45	7.95	8.75	24.0
	124818	ZS 2090	2 x 18	5.00	8.80	9.55	28.0
	124820	ZS 2099	2 x 20	5.55	9.85	10.60	33.8

MOUNTER® COMBINATION LADDER - aluminium ladder (black coated)

Description	Art.No.	Type	Number of rungs	Storage length (m)	Extended length (m)	Max. working height A-position (m)	Max. working height (m)	Weight (kg)
2-part combination ladder	122408	ZR 2040	2 x 8	2.26	3.90	3.20	4.85	13.9
	122410	ZR 2050	2 x 10	2.80	5.00	3.75	5.90	16.2
	122412	ZR 2060	2 x 12	3.34	6.05	4.30	6.95	18.6
	122414	ZR 2070	2 x 14	3.88	6.90	4.75	7.75	21.0
3-part combination ladder	123608	ZR 3055	3 x 8	2.27	5.30	4.00	6.20	18.8
	123610	ZR 3072	3 x 10	2.81	6.65	4.55	7.50	23.9
	123612	ZR 3083	3 x 12	3.35	8.00	5.10	8.80	28.3
	123614	ZR 3099	3 x 14	3.89	8.80	5.60	9.55	35.2