

Altrex RS TOWER 54

A compact folding scaffold for professional service and maintenance. The folding base makes it practical to move between work areas and store after use, while the RS TOWER 5 system allows the tower to grow with the task.

Features

- 0.75 m frame width and 1.85 m Fiber-Deck platform
- Selected working heights from 2.70 to 6.80 m
- Braced and Safe-Quick configurations

Selected configurations

Max Working Height	Platform height	Article number	Assembly method
2.7 m	0.7 m	T540002	Braces
3.6 m	1.6 m	T540004	Braces
4.8 m	2.8 m	T540014	Safe-Quick®
6.8 m	4.8 m	T540016	Safe-Quick®

The 2.70 and 3.60 m versions use braces. The selected 4.80 and 6.80 m versions use Safe-Quick guardrails. Working height and platform height are listed separately to support accurate selection.

Safety and quality

Altrex manufactures its scaffold systems in its own factory in the Netherlands. Current tower configurations are designed around EN 1004 requirements.

Follow the supplied instructions and assess the working location. Working height is approximate reach height, not platform height. Tower assembly, stabilisers and permitted indoor/outdoor heights depend on the complete configuration.

Prepared by MariTeam from Altrex specifications. This product summary is not a manufacturer certificate or assembly manual. Reviewed 8 September 2026.

Source: <https://altrex.com/en/scaffolding/rs-tower-54-folding-tower/2040>